



View more

S300 Surveillance Hard Drives

Always On, Always Watching

With surveillance systems, nothing but the best is good enough. The Toshiba 3.5-inch S300 is built to meet the highest demands. With support for up to 64 high-resolution surveillance video cameras simultaneiously and up to 6 TB capacity, it brings everything into clear view. Each S300 is built with the highest-quality components and has passed rigorous tests to ensure 24x7 reliability and performance. That's Toshiba quality you can trust under the harshest working conditions.

Use for

- Surveillance Digital Video Recorders (sDVR)
- Surveillance Network Video Recorders (sNVR)
- Hybrid sDVR (analog and IP)

Top Features

3.5" SATA Hard Drive SATA

RPM 5,400 rpm

256 MB buffer (6 | 4 TB) 128 MB buffer (2 TB)

Up to 64 cameras

24/7 24/7 operation

Capacities



S300 Surveillance Hard Drive – 6 TB

Retail Number	n/a
Bulk Number	HDWT860UZSVA
Basic Specifications	
Form factor	3.5-inch
Interface	SATA 6.0 Gbit/s
Recording Technology	SMR
Number of cameras supported	64
Drive bays supported	up to 8
Shock Sensor	yes
Advanced Format (AF)	yes
RoHS compatible	yes
Halogen free	yes
Performance	
Rotational speed (rpm)	5,400
Max. data transfer speed (sustained MB/s Typ.)	184
Buffer size (MB)	256
Reliability	
Workloads (TB/year)	180
MTTF (hours)	1,000,000
Unrecoverable error rate	1 per 10^14
24 x 7 operation	yes
Load/Unload cycle	600,000
Limited warranty (years)	3
	j
Power Management	
Supply voltage	5 V DC ±5 % 12 V DC ±10 %
Consumption (operating)	4.84 W typ.
Consumption (active idle)	2.81 W typ.
Environmental	
Temperature	0 to 70 °C
(operating/non-operating)	-40 to 70 °C
Vibration (operating)	4.90 m/s2 {0.50 G}(5 to 350 Hz) 2.45 m/s2 {0.25 G}(350 to 500 Hz)
Vibration (non-operating)	29.4 m/s2 {3.0 G} (5 to 500 Hz)
Shock (operating)	686 m/s2 {70 G} (2 ms duration)
Shock (non-operating)	2,940 m/s2 {300 G} (2 ms duration)
Acoustics (idle mode)	24 dB typ.
Physical	
Physical Dimensions	147 (L) x 101.85 (W) x 26.1 (H) mm



S300 Surveillance Hard Drive – 6 TB

Retail Number	n/a
Bulk Number	HDWT860UZSVA
Logistic Information (Bulk)	
Master Carton quantity	20 pcs
Master Carton size	321 (L) x 406 (W) x 213 (H) mm
Master Carton Weight	16 kg
Pallet quantity per layer	180 pcs
Number of Layer	4 layer
Pallet quantity	720 pcs
Pallet size	1,250 (L) x 1,030 (W) x 1,030 (H) mm
Pallet weight	553 kg
Country of Origin	China



S300 Surveillance Hard Drive – 4 TB

Retail Number	n/a	
Bulk Number	HDWT840UZSVA	
Basic Specifications		
Form factor	3.5-inch	
Interface	SATA 6.0 Gbit/s	
Recording Technology	SMR	
Number of cameras supported	64	
Drive bays supported	up to 8	
Shock Sensor	yes	
Advanced Format (AF)	yes	
RoHS compatible	yes	
Halogen free	yes	
Performance		
Rotational speed (rpm)	5,400	
Max. data transfer speed (sustained MB/s Typ.)	184	
Buffer size (MB)	256	
Reliability		
Workloads (TB/year)	180	
MTTF (hours)	1,000,000	
Unrecoverable error rate	1 per 10^14	
24 x 7 operation	yes	
Load/Unload cycle	600,000	
Limited warranty (years)	3	
Power Management		
Supply voltage	5 V DC ±5 % 12 V DC ±10 %	
Consumption (operating)	4.36 W typ.	
Consumption (active idle)	2.33 W typ.	
Environmental		
Temperature (operating/non-operating)	0 to 70 °C -40 to 70 °C	
Vibration (operating)	4.90 m/s2 {0.50 G}(5 to 350 Hz) 2.45 m/s2 {0.25 G}(350 to 500 Hz)	
Vibration (non-operating)	29.4 m/s2 {3.0 G} (5 to 500 Hz)	
Shock (operating)	686 m/s2 {70 G} (2 ms duration)	
Shock (non-operating)	3,430 m/s2 {350 G} (2 ms duration)	
Acoustics (idle mode)	22 dB typ.	
Physical		
Dimensions	147 (L) x 101.85 (W) x 26.1 (H) mm	

650 g

Country of Origin



S300 Surveillance Hard Drive – 4 TB

Retail Number	n/a
Bulk Number	HDWT840UZSVA
Logistic Information (Bulk)	
Master Carton quantity	20 pcs
Master Carton size	321 (L) x 406 (W) x 213 (H) mm
Master Carton Weight	16 kg
Pallet quantity per layer	180 pcs
Number of Layer	4 layer
Pallet quantity	720 pcs
Pallet size	1,250 (L) x 1,030 (W) x 1,030 (H) mm
Pallet weight	373 ka

China



S300 Surveillance Hard Drive – 2 TB

Retail Number	n/a
Bulk Number	HDWT720UZSVA
	115111120020111
Basic Specifications	
Form factor	3.5-inch
Interface	SATA 6.0 Gbit/s
Recording Technology	SMR
Number of cameras supported	64
Drive bays supported	up to 8
Shock Sensor	yes
Advanced Format (AF)	yes
RoHS compatible	yes
Halogen free	yes
Performance	
Rotational speed (rpm)	5,400
Max. data transfer speed	
(sustained MB/s Typ.)	184
Buffer size (MB)	128
Reliability	
Workloads (TB/year)	180
MTTF (hours)	1,000,000
Unrecoverable error rate	1 per 10^14
24 x 7 operation	yes
Load/Unload cycle	600,000
Limited warranty (years)	3
	o
Power Management	
Supply voltage	5 V DC ±5 % 12 V DC ±10 %
Consumption (operating)	4.01 W typ.
Consumption (active idle)	2.08 W typ.
	,
Environmental	
Temperature	0 to 70 °C
(operating/non-operating)	-40 to 70 °C
Vibration (operating)	4.90 m/s2 {0.50 G}(5 to 350 Hz) 2.45 m/s2 {0.25 G}(350 to 500 Hz)
Vibration (non-operating)	29.4 m/s2 {3.0 G} (5 to 500 Hz)
Shock (operating)	686 m/s2 {70 G} (2 ms duration)
Shock (non-operating)	3,430 m/s2 {350 G}
	(2 ms duration)
Acoustics (idle mode)	21 dB typ.
Physical	
Dimensions	147 (L) x 101.85 (W) x 26.1 (H) mm
Weight	440 g

Country of Origin



S300 Surveillance Hard Drive – 2 TB

Retail Number	n/a
Bulk Number	HDWT720UZSVA
Logistic Information (Bulk)	
Master Carton quantity	20 pcs
Master Carton size	321 (L) x 406 (W) x 213 (H) mm
Master Carton Weight	16 kg
Pallet quantity per layer	180 pcs
Number of Layer	4 layer
Pallet quantity	720 pcs
Pallet size	1,250 (L) x 1,030 (W) x 1,030 (H) mm
Pallet weight	371 kg

China