

TOSHIBA



[View more](#)

S300 AI Surveillance Hard Drives

Reliable. Scalable. AI-ready.

The Toshiba S300 AI Surveillance Hard Drive is designed for professional environments and large-scale surveillance infrastructures. Its firmware OptiFrame™ AI is optimized for AI-enhanced environments, ensuring smooth operation. Supporting up to 24 TB of storage, it can manage video feeds from up to 64 cameras while delivering real-time AI analytics on 32 simultaneous streams – all without dropping a single frame. Designed for nonstop operation, it ensures seamless capture and analysis of large data volumes – keeping your system responsive and reliable, even under a heavy load.

Use for

- AI Video Analytics Server and Storage Systems
- Centralized Surveillance Data Storage Systems
- Video Archive and Data Recovery Systems
- Multi-Bay-RAID Storage for Surveillance Data

Top Features

- SATA** 3.5" SATA Hard Drive
- RPM** 7,200 rpm
- 512/1024 MB** buffer
- 24/7** 24/7 operation
- OptiFrame™ AI** Technology
- Supports up to 64** video cameras
- Supports up to 32** AI streams
- 550** 550 TB/year workload
- 5** 5-year warranty

Capacities

24 TB	22 TB	20 TB	18 TB
16 TB	14 TB	10 TB	8 TB



S300 AI

 Surveillance Hard Drives

	24 TB	22 TB	20 TB	18 TB	16 TB	14 TB	10 TB	8 TB
Retail Number	HDWTB2EEZSTA	HDWTB2CEZSTA	HDWTB2AEZSTA	HDWTB1JEZSTA	HDWTB1GEZSTA	HDWTB1EEZSTA	HDWTA1AEZSTA	HDWTA80EZSTA
Bulk Number	MG11ACA24TE-V	MG11ACA22TE-V	MG11ACA20TE-V	MG11ACA18TE-V	MG11ACA16TE-V	MG11ACA14TE-V	MG10ADA10TE-V	MG10ADA800E-V

Basic Specifications

Form factor	3.5-inch							
Interface	SATA 6.0 Gbit/s							
Recording Technology	CMR							
Number of cameras supported	64							
AI Streams supported	32							
Drive bays supported	24							
Shock Sensor	yes							
Native command queuing (NCQ)	yes							
Advanced Format (AF)	yes							
RoHS compatible	yes							
Halogen free	yes							

Performance

Rotational speed (rpm)	7,200			
Max. data transfer speed (sustained MB/s Typ.)	309	299	295	281
Buffer size (MB)	1,024			512

Reliability

Workloads (TB/year)	550	
MTTF (hours)	2,500,000	2,000,000
Unrecoverable error rate	1 per 10^15	
24 x 7 operation	yes	
Load/Unload cycle	600,000	
Limited warranty (years)	5	

Power Management

Supply voltage	5 V DC +10/-7 % 12 V DC ±10 %							
Consumption (operating)	7.65 W typ.			7.51 W typ.	7.04 W typ.		8.47 W typ.	
Consumption (active idle)	4.35 W typ.			4.16 W typ.	3.66 W typ.		4.92 W typ.	

Environmental

Temperature (operating/non-operating)	5 to 60 °C -40 to 70 °C							
Vibration (operating)	7.35 m/s2 {0.75 G} (5 to 300 Hz) 2.45 m/s2 {0.25 G} (300 to 500 Hz)							
Vibration (non-operating)	29.4 m/s2 {3.0 G} (5 to 500 Hz)							
Shock (operating)	490 m/s2 {50 G} (2 ms duration)						686 m/s2 {70 G} (2 ms duration)	
Shock (non-operating)	1,960 m/s2 {200 G} (2 ms duration)						2,450 m/s2 {250 G} (2 ms duration)	
Acoustics (idle mode)	20 dB typ.						34 dB typ.	

Physical

Dimensions	147 (L) x 101.85 (W) x 26.1 (H) mm							
Weight	730 g						755 g	

Logistic Information (Bulk)

Master Carton quantity	20 pcs							
Master Carton size (L x B x H)	410 x 308 x 228 mm							
Master Carton Weight	17 kg							
Pallet quantity per layer	120 pcs							
Number of Layer	5 layer							
Pallet quantity	600 pcs							
Pallet size (L x W x H)	870 x 970 x 1,272 mm							
Pallet Weight	464 kg	486 kg	455 kg	456 kg	441 kg	441 kg	510 kg	495 kg
Country of Origin	Philippines							